
# **PLACE**

## Pendant downlights







#### 109PLC.1.02-I720



IP20 650°





Pendant downlights with symmetrical light distribution to achieve an effective ambient lighting. Circular design available in 553mm diameter.

Powder painted one piece aluminium profile available in assorted finishes, customized RAL under request.

PMMA opal diffuser (thickness 3mm.).

Tridonic high energy efficiency printed circuit board. Tunable White PCB: 2700K - 6500K Built-in driver, included.

Electronic options for lighting control: SwitchDIM/ColourSwitch/DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits:  $PstLM \le 1$  and  $SVM \le 0.4$ .

Passive temperature management: heat dissipation flows through the fixture body itself.

Ceiling-mounted using ceiling rose. Suspended 1 meter by four steel cords. Transparent electronic wire. PLACE can be combined with KUU and CANDRA recessed downlights and LEDA surface-mounted downlights to get a harmonious finish.

lmax=1349 Cd

500

1000

η=99.6% ▼ M ▼ Ø ▼ LUX

2

3

4 9.8 84

2.5 1349

12.3

4.9 337

7.4 150

102°

Luminaire luminous flux: 3470lm Luminaire connected power: 29,9 W Luminaire efficiency: 116 lm/W Light source luminous flux: 4650lm

**Light source power:** 28 W **Constant Current:** 125 mA

**CRI:** >90

**Colour Temperature:** 2700K-6500K **Chromaticity Tolerance:** MacAdam 3

Beam Angle: 102°

LED reliability at nominal Ta = 25°C: 50.000h L90B50

Photobiological safety group: 1

This product contains a light source of energy efficiency class D

### **Electronic Equipment**

T: Tunable White DALI-2/switchDIM/ColourSwitch

\*Add the suffix -T after the reference to indicate your electronic equipment choice.

#### **Finishes**

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 01.11.2025]

5 years guarantee



Spain

d. La Gavarra T. +34 93 881 37 13