

## 110PLC.1.02-I721



IP20

650°



8.07Kg

Pendant downlights with symmetrical light distribution to achieve an effective ambient lighting.  
Circular design available in 835mm diameter.  
Powder painted one piece aluminium profile available in assorted finishes, customized RAL under request.

PMMA opal diffuser (thickness 3mm.).

Tridonic high energy efficiency printed circuit board. Tunable White PCB: 2700K - 6500K

Built-in driver, included.

Electronic options for lighting control: SwitchDIM/ColourSwitch/DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.

Passive temperature management: heat dissipation flows through the fixture body itself.

Ceiling-mounted using ceiling rose. Suspended 1 meter by four steel cords. Transparent electronic wire.

PLACE can be combined with KUU and CANDRA recessed downlights and LEDA surface-mounted downlights to get a harmonious finish.

**Luminaire luminous flux:** 6605lm

**Luminaire connected power:** 59.9 W

**Luminaire efficiency:** 110 lm/W

**Light source luminous flux:** 9610lm

**Light source power:** 58 W

**Constant Current:** 250 mA

**CRI:** >90

**Colour Temperature:** 2700K-6500K


**Chromaticity Tolerance:** MacAdam 3

**Beam Angle:** 102°

**LED reliability at nominal Ta = 25°C:** 50000h L90B50

**Photobiological safety group:** 1

**This product contains a light source of energy efficiency class D**



### Electronic Equipment

**T:** Tunable White DALI-2/switchDIM/ColourSwitch

\*Add the suffix **-T** after the reference to indicate your electronic equipment choice.

### Finishes

**1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

### Upgradeable, Replaceable, Repairable



### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 01.07.2025]

### 5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

### ROVASI S.L.

Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

### Contact

T. +34 93 881 35 12  
T. +34 93 881 37 13

info@rovasi.com

[www.rovasi.com](http://www.rovasi.com)