
# **MOVE 100**

# Spots with recessed base







## 107MOV.1-R1147



IP20 850°







Recessed spots with symmetrical light distribution to achieve an effective task, accent or general lighting. Special LED module created to be the optimal solution for specific projects.

Cylindrical design in diameter 120mm.

Articulated arm adjustable 0°,15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical

Facetted metalized or sandblasted metalized aluminium reflector.

Powder painted aluminium body and arm available in assorted finishes, customized RAL under request. Die-cast aluminium recessed base supplied with the same finish as the light fixture.

Optional anti-glare accessories for more visual comfort.

Remote driver included.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4.

max=14868 Cd

η=90.7% ▼ M ▼ Ø ▼ LUX

2

3

4 0.86 929

0.22 14868

0.65 1652

1.08

3717 0.43

Passive temperature management: heat dissipation flows through aluminium heat sink.

Mounted to the ceiling by two fixing points.

Luminaire luminous flux: 1488lm Luminaire connected power: 12.61 W Luminaire efficiency: 118 lm/W Light source luminous flux: 1635lm

Light source power: 11 W Constant Current: 350 mA

**CRI:** >90

Colour Temperature: GOLD

Chromaticity Tolerance: MacAdam 3

Beam Angle: 12° **LOR:** 91%

**LED** reliability at nominal Ta = 25°C: 50000h L90B50

 $\mbox{\bf UGR:}~C0^{o}=13,3~|~C90^{o}=13,3~$  under the below indicated parameters Room dimensions X=4H/8H

Reflectance 20% | 50% | 70% Luminaire spacing = 0.25m

Photobiological safety group: 1

This product contains a light source of energy efficiency class  $\[ \]$ 

#### **Electronic Equipment**

K: On/Off (basic)
S: On/Off (AC/DC, NOT looping through capable)
SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION

DE: DALI-2/switchDIM + 3h battery

B: Bluetooth-Casambi

\*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

### **Finishes**

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 31.10.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASIS.L.** 

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Contact

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13