

# MOVE 100

## Spots with recessed base









### 111MOV.1-R870



IP20 850°









lmax=26098 Cd

η=90.7% ▼ M ▼ Ø ▼ LUX

1

2 0.43 6524

3 0.65

4

1.08 1044

0.22 26098

1631 0.86

12°

Recessed spots with symmetrical light distribution to achieve an effective task, accent or general lighting. Cylindrical design in diameter 140 mm.

Articulated arm adjustable 0°,15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical

Facetted metalized or sandblasted metalized aluminium reflector.

Powder painted aluminium body and arm available in assorted finishes, customized RAL under request.

Die-cast aluminium recessed base supplied with the same finish as the light fixture.

Optional anti-glare accessories for more visual comfort.

Remote driver included.

Passive temperature management: heat dissipation flows through aluminium heat sink.

Mounted to the ceiling by two fixing points.

Luminaire luminous flux: 2612lm Luminaire connected power: 18.33 W Luminaire efficiency: 142 lm/W Light source luminous flux: 2870lm

Light source power: 17 W Constant Current: 500 mA

**CRI:** >80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 12°

**LOR:** 91%

Average Service Life: 50000h LED reliability: 50000h L90B10

**UGR:** <16

Photobiological safety group: 1

This product contains a light source of energy efficiency class D

#### **Electronic Equipment**

K: On/Off (basic)
S: On/Off (AC/DC)

SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM + 3h battery

B: Bluetooth-Casambi

## **Finishes**

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 02.05.2024]

5 years guarantee



Spain

T. +34 93 881 37 13

<sup>\*</sup>Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.