


111MOV.1-R691



Recessed spots with symmetrical light distribution to achieve an effective task, accent or general lighting. Special LED module created to be the optimal solution for specific projects. Cylindrical design in diameter 140 mm. Articulated arm adjustable 0°, 15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical axis. Facetted metalized or sandblasted metalized aluminium reflector. Powder painted aluminium body and arm available in assorted finishes, customized RAL under request. Die-cast aluminium recessed base supplied with the same finish as the light fixture. Optional anti-glare accessories for more visual comfort. Remote driver included. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0,4. Luminaire designed according to ecodesign principles, with replaceable light source and driver, to enable upgrades, ease maintenance and extend the product lifecycle. Passive temperature management: heat dissipation flows through aluminium heat sink. Mounted to the ceiling by two fixing points.

Luminaire luminous flux: 1729lm
Luminaire connected power: 25,33 W
Luminaire efficiency: 68 lm/W
Light source luminous flux: 1900lm
Light source power: 23 W
Constant Current: 700 mA
CRI: >90
Colour Temperature: FRESH MEAT
Chromaticity Tolerance: MacAdam 4
Beam Angle: 12°
LOR: 91%
LED reliability at nominal Ta = 25°C: 50000h L90B50
UGR: C0° = 14 | C90° = 14 under the below indicated parameters
Room dimensions X=4H/8H
Reflectance 20% | 50% | 70%
Luminaire spacing = 0.25m
Photobiological safety group: 1



Electronic Equipment
K: On/Off (basic)
S: On/Off (AC/DC, NOT looping through capable)
SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM + 3h battery
B: Bluetooth-Casambi

*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes
1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 14.12.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com