# MOVE 100

## Spots with recessed base



η=91.3% ▼ M ▼ Ø ▼ LUX

1

2 0.57 7483

4


0.28 29933


1871 1.13

0.85

1.42 1197 16°







## 111MOV.1-R1110



IP20











lmax=29933 Cd

Recessed spots with symmetrical light distribution to achieve an effective task, accent or general lighting. Cylindrical design in diameter 140 mm.

Articulated arm adjustable 0°,15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical

Facetted metalized or sandblasted metalized aluminium reflector.

Powder painted aluminium body and arm available in assorted finishes, customized RAL under request.

Die-cast aluminium recessed base supplied with the same finish as the light fixture.

Optional anti-glare accessories for more visual comfort.

Remote driver included.

Passive temperature management: heat dissipation flows through aluminium heat sink.

Mounted to the ceiling by two fixing points.

Luminaire luminous flux: 4473lm Luminaire connected power: 33.05 W Luminaire efficiency: 135 lm/W Light source luminous flux: 4915lm

Light source power: 30 W Constant Current: 900 mA

**CRI:** >80

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 12°

**LOR:** 91%

Average Service Life: 50000h LED reliability: 50000h L90B10

**UGR:** <19

Photobiological safety group: 1

This product contains a light source of energy efficiency class D

#### **Electronic Equipment**

K: On/Off (basic)
S: On/Off (AC/DC)

SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM + 3h battery

B: Bluetooth-Casambi

## **Finishes**

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 02.05.2024]

5 years guarantee



Spain

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13

<sup>\*</sup>Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.