

# MOVE 300 OPTIMAL DISPLAY



Surface-mounted spots









### 311MOV.1-I1148



Surface-mounted spots with symmetrical light distribution to achieve an effective task, accent or general lighting.

Special LED module created to be the optimal solution for specific projects.

Cylindrical design in diameter 140 mm. Articulated arm adjustable 0°,15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical axis.

Facetted metalized or sandblasted metalized aluminium reflector.


Powder painted aluminium body and arm available in assorted finishes, customized RAL under request. Aluminium base for attachment to the ceiling supplied with the same finish as the light fixture. Optional anti-glare accessories for more visual comfort.

Integral driver included.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4.

Passive temperature management: heat dissipation flows through aluminium heat sink. Mounted to the ceiling by two fixing points.

Luminaire luminous flux: 1006lm Luminaire connected power: 12.61 W Luminaire efficiency: 80 lm/W Light source luminous flux: 1105lm Light source power: 11 W Constant Current: 350 mA CRI: >90 Colour Temperature: GOLD+ Chromaticity Tolerance: MacAdam 4 Beam Angle: 12° LOR: 91% Average Service Life: 50000h LED reliability: 50000h L90B50 Photobiological safety group: 1



This product contains a light source of energy efficiency class G

#### **Electronic Equipment**

K: On/Off (basic) S: On/Off (AC/DC) D: DALI-2/switchDIM/corridorFUNCTION

\*Add the suffix -K, -S, -D after the reference to indicate your electronic equipment choice.

#### Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

#### Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 11.05.2025]

## 5 years guarantee

**L C** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### ROVASI S.L.

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Ronda de la Font Grossa, 15 T. +

#### Contact

T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com