

# MOVE 900

## Track spots











### 907MOV.1-T865



IP20 850°





Track spots with symmetrical light distribution to achieve an effective task, accent or general lighting. Cylindrical design in diameter 120mm.

Articulated arm adjustable 0°,15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical

Facetted metalized or sandblasted metalized aluminium reflector.

Powder painted aluminium body and arm available in assorted finishes, customized RAL under request.

Track adaptor available in white, black or grey.

Optional anti-glare accessories for more visual comfort.

Driver built into the track adaptor. Consult compatible tracks with the track adaptor. Passive temperature management: heat dissipation flows through aluminium heat sink.

Three-phase tracks are available as well as accessories to create a custom system.

Luminaire luminous flux: 1934lm Luminaire connected power: 12.61 W Luminaire efficiency: 153 lm/W Light source luminous flux: 2125lm

Light source power: 11 W Constant Current: 350 mA

**CRI:** >80

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 12°

**LOR:** 91%

Average Service Life: 50000h LED reliability: 50000h L90B10 Photobiological safety group: 1

This product contains a light source of energy efficiency class D

### lmax=19323 Cd η=90.7% ▼ M ▼ Ø ▼ LUX 12° 0.22 19323 1 0.43 4831 0.65 3 4 1208 0.86 773 1.08

### **Electronic Equipment**

D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

\*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 12.05.2024]

5 years guarantee



Spain

T. +34 93 881 37 13