
MOVE 900

Track spots








907MOV.1-T881



IP20 850°





Articulated arm adjustable 0°,15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical

Facetted metalized or sandblasted metalized aluminium reflector.

Powder painted aluminium body and arm available in assorted finishes, customized RAL under request. Track adaptor available in white, black or grey.

Optional anti-glare accessories for more visual comfort.

Driver built into the track adaptor. Consult compatible tracks with the track adaptor.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.

lmax=23752 Cd

η=91.3% ▼ M ▼ Ø ▼LUX

0.28 23752

0.85

1.13 1484

1.42 950

1

2 0.57 5938

4

16°

Passive temperature management: heat dissipation flows through aluminium heat sink.

Three-phase tracks are available as well as accessories to create a custom system.

Luminaire luminous flux: 3549lm Luminaire connected power: 25.33 W Luminaire efficiency: 140 lm/W Light source luminous flux: 3900lm

Light source power: 23 W Constant Current: 700 mA

CRI: >80

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 12° **LOR:** 91%

LED reliability at nominal Ta = 25°C: 50000h L90B10

Photobiological safety group: 1

This product contains a light source of energy efficiency class D

Electronic Equipment

S: On/Off

D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 13.06.2025]

5 years guarantee



Spain

T. +34 93 881 37 13