

MOVE 900

Track spots










911MOV.1-T864



IP20 850°





Cylindrical design in diameter 140 mm.

Activulated arm adjustable 0° 15° 30° 45° 60° 75° and 90° and with 355° rotation around the vertical

Articulated arm adjustable 0° , 15° , 30° , 45° , 60° , 75° and 90° and with 355° rotation around the vertical axis.

Facetted metalized or sandblasted metalized aluminium reflector.

Powder painted aluminium body and arm available in assorted finishes, customized RAL under request.

Track adaptor available in white, black or grey.

Optional anti-glare accessories for more visual comfort.

Driver built into the track adaptor. Consult compatible tracks with the track adaptor. Passive temperature management: heat dissipation flows through aluminium heat sink.

Three-phase tracks are available as well as accessories to create a custom system.

Luminaire luminous flux: 1856lm Luminaire connected power: 12.61 W Luminaire efficiency: 147 lm/W Light source luminous flux: 2040lm

Light source power: 11 W **Constant Current:** 350 mA

CRI: >80


Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 12° LOR: 91%

Average Service Life: 50000h LED reliability: 50000h L90B10 Photobiological safety group: 1

This product contains a light source of energy efficiency class D



Electronic Equipment

S: On/Of

D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 03.05.2024]

5 years guarantee



Spain