
SUMMIT Pendant downlights





101SMM.1-I874



Pendant downlight with symmetrical light distribution to achieve an effective task or ambient lighting. Facetted metallized aluminium reflector to control and direct the light. Powder painted aluminium body available in assorted finishes, customized RAL under request.

Built-in driver, included.


Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself.

Delivered with 1 meter steel cord suspension as standard and Transparent electronic wire. Mounted to the ceiling by cylindrical ceiling rose.

For a more dynamic result, it can be supplied with an adapter for three-phase track [reference M3.B].

Luminaire luminous flux: 2321lm Luminaire connected power: 18.33 W Luminaire efficiency: 127 lm/W Light source luminous flux: 2550lm Light source power: 17 W Constant Current: 500 mA **CRI:** >90 Colour Temperature: 4000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 12° LOR: 91% Average Service Life: 50000h LED reliability: 50000h L90B10 **UGR:** <16 Photobiological safety group: 1 Cd/Klm: 9093 Imax: 23187 Cd This product contains a light source of energy efficiency class E



Electronic Equipment

S: On/Off D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]

5 years guarantee BSI Cert ISO 9001:2015 - nºFM 39346

BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Contact Ronda de la Font Grossa, 15 T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com

