

SAUCER

IP65 Pendant downlights for catenary systems

ROVASI
Positive Lighting








101SCR.1.01-I863

IP65 | IK10 | 850º | + INSTAL | +RAL | 2.52Kg

Vandal-resistant pendant downlights with symmetrical light distribution.
Circular design in diameter 265mm.
Protection rating against dust and moisture: complete IP65.
Protection rating for resistance to harmful mechanical impacts: IK10.
Robust body made of die-cast aluminium and trim coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.
Sandablasted metallized aluminium reflector.
Impact resistant cover made of clear polycarbonate (IK10) as standard.
Temperature resistant silicone rubber gasket.
Anti-condensation device.
A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screws [reference F2.A0265+F2.A1].
Built-in driver, included.
Electronic options for lighting control: DALI/DSI.
Passive temperature management: heat dissipation via the fixture body itself.
Cable hanger made in stainless steel 316L. Adjustable 0º, 5º, 10º,15º or 20º to compensate for sloping catenary system.
Cable entry from the top of the fixture. Double cable gland entry for installation in series.
Suggested applications : arcades, galleries, passageways, streets.



▼M	▼Ø	▼LUX
1	2.5	579
2	4.9	145
3	7.4	64
4	9.9	36
5	12.3	23

Lichtquelle-Anschlussleistung: 11 W
Anschlussleistung: 12.61 W
Konstantstromquelle: 350 mA
Lichtquelle Lichtstrom: 1960lm
Leuchten Lichtstrom: 1235lm
Farbwiedergabeindex: >80
Ähnlichste Farbtemperatu: 2700K
Farborttoleranz: MacAdam 3
Winkel: 102º
LOR: 63%
Durchschnittliche Betriebsdauer: 50000h
Durchschnittliche Betriebsdauer: 50000h L90B10
Photobiologische Sicherheit Gruppe: 1
Cd/Klm: 295
Leuchten Lichtausbeute: 98 lm/W
Imax: 578 Cd
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse D


Elektronische Ausrüstung


S: On/Off
SE: On/Off + 3 hours battery [class I]
D: DALI-2/DSI/switchDIM
DE: DALI-2/DSI/switchDIM+3 hours battery [class I]
DDE: DALI-2/DSI/switchDIM+3 hours battery (DALI) [class I]
There are accessories available for dimming devices.
*Ein beliebiges vorgenanntes Suffix **-S, -SE, -D, -DE, -DDE** zur Referenz hinzufüge, um die gewünschte elektronische Ausrüstung anzugeben.

Finishes

1: RAL9010: Reinweiß, **2:** RAL9005: Tiefschwarz, **4:** RAL7016: Anthrazitgrau, **7:** RAL9006: Weißaluminium

Aufrüstbar, austauschbar, reparierbar





Anmerkung

Die LED-Technologie und Leistungsdaten sind einem ständigen Wandel unterworfen. Aktuelle Details müssen daher bei ROVASI nachgefragt werden, um sicherzustellen, dass die Daten aktuell sind. Aktualisierte Daten werden auf Anfrage bereitgestellt. [Letzte Revision 29.03.2024].

5 jahre garantie

CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spanien

Kontakt
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**