
HANDY
IP68 Projektoren

ROVASI
Positive Lighting






104HNY.4.01-I865

IP68 | IK10 | 850º | +ELEC | +RAL | 1.95Kg

Projector with symmetrical light distribution.
Circular design in diameter: 134mm.
Complete IP68 protection.
Protection rating of resistance to harmful mechanical impacts: IK10.
>Robust body and trim made of die-cast aluminium coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.
Sandblasted metalized aluminium reflector.
15 mm tempered protection glass clear as standard, other finishes under request.
Temperature resistant silicone rubber gasket.
A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screws [reference F2.A0134+F2.A1].
Built-in driver, included.
Electronic options for lighting control: DALI.
Passive temperature management: heat dissipation flows through the fixture body itself.
Mounting to the ceiling, to the wall or to the floor by support with two securing holes that enables the device to be swivelled and adjusted to achieve specific lighting effects.
Cable entry from the top of the fixture.
Double cable gland entry for installation in series.
Pre-wiring of 0.5 metres cable 3x1mm2.
IP68 connector to be ordered separately [reference F3.A3 (On/Off) / F3.A5 (DALI)].

Lichtquelle-Anschlussleistung: 11 W
Anschlussleistung: 12.61 W
Konstantstromquelle: 350 mA
Lichtquelle Lichtstrom: 2125lm
Leuchten Lichtstrom: 1414lm
Farbwiedergabeindex: >80
Ähnlichste Farbtemperatu: 4000K
Farborttoleranz: MacAdam 3
Winkel: 89º
Durchschnittliche Betriebsdauer: 50000h
Durchschnittliche Betriebsdauer: 50000h L90B10
Photobiologische Sicherheit Gruppe: 1
Leuchten Lichtausbeute: 112 lm/W
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse D





▼M	▼Ø	▼LUX	89°
1	1.97	851	
2	3.9	213	
3	5.9	95	
4	7.9	53	
5	9.8	34	

Elektronische Ausrüstung
S: On/Off
D: DALI-2
*Ein beliebiges vorgenanntes Suffix **-S, -D** zur Referenz hinzufüge, um die gewünschte elektronische Ausrüstung anzugeben.

Finishes
1: RAL9010: Reinweiß, **2:** RAL9005: Tiefschwarz, **4:** RAL7016: Anthrazitgrau, **7:** RAL9006: Weißaluminium

Aufrüstbar, austauschbar, reparierbar





Anmerkung

Die LED-Technologie und Leistungsdaten sind einem ständigen Wandel unterworfen. Aktuelle Details müssen daher bei ROVASI nachgefragt werden, um sicherzustellen, dass die Daten aktuell sind. Aktualisierte Daten werden auf Anfrage bereitgestellt. [Letzte Revision 29.03.2024].

5 jahre garantie

CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spanien

Kontakt
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**