UNEDO 400
IP66 Wandmontierte


ROVASI
Positive Lighting



430UND.4-I1172



Wall-mounted fixture with 360º light emission, radial beam.
Cylindrical design with a diameter of 140mm.
Luminaire height: 300mm.
Protection rating against dust and moisture: IP66 – full protection.
Protection rating for resistance against harmful mechanical impacts: IK10.
Die-cast aluminium body and top cover made of die-cast aluminium coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.
5mm extruded polycarbonate diffuser made by resins UV stabilized. Opal finish.
A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screw.
Silicone gasket.
Anticondensation device.
PCB on the top of the fixture.
Built-in driver included. Ambient temperature: up to 50ºC.
Electronic options for light control: DALI.
Pre-wiring with 25cm of 3x1mm2 cable.
Double cable gland entry for installation in series.
IP68 connector not included, it can be ordered separately: F3.A3 (On/Off) / F3.A5 (DALI) .
Mounting to the wall through mounting plate with two fixing holes. Cable entry from the mounting plate.




C0 / C90	d=0	d=1	d=2	d=3	d=4
h=1	1.2 / 1.2	5.0 / 5.0	2.6 / 2.6	1.1 / 1.1	0.5 / 0.5
h=2	0.3 / 0.3	0.5 / 0.5	1.3 / 1.3	1.1 / 1.1	0.7 / 0.7
h=3	0.1 / 0.1	0.1 / 0.1	0.4 / 0.4	0.6 / 0.6	0.5 / 0.5
h=4	0.1 / 0.1	0.1 / 0.1	0.1 / 0.1	0.3 / 0.3	0.3 / 0.3
h=5	0.0 / 0.0	0.0 / 0.0	0.0 / 0.0	0.1 / 0.1	0.2 / 0.2


Lichtquelle-Anschlussleistung: 7,5 W
Anschlussleistung: 7.5 W
Konstantstromquelle: 350 mA
Lichtquelle Lichtstrom: 774lm
Leuchten Lichtstrom: 341lm
Farbwiedergabeindex: 93
Ähnlichste Farbtemperatu: 2700K
Farborttoleranz: MacAdam 4
Winkel: 360º
LOR: 44%
Durchschnittliche Betriebsdauer: 50000h
Durchschnittliche Betriebsdauer: 52000h L80B50
Photobiologische Sicherheit Gruppe: 1
Leuchten Lichtausbeute: 45 lm/W
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse consult

Elektronische Ausrüstung
S: On/Off
D: DALI-2
*Ein beliebiges vorgenanntes Suffix **-S, -D** zur Referenz hinzufüge, um die gewünschte elektronische Ausrüstung anzugeben.

Finishes
1: RAL9010: Reinweiß, **2:** RAL9005: Tiefschwarz, **4:** RAL7016: Anthrazitgrau, **7:** RAL9006: Weißaluminium

Aufrüstbar, austauschbar, reparierbar





Anmerkung

Die LED-Technologie und Leistungsdaten sind einem ständigen Wandel unterworfen. Aktuelle Details müssen daher bei ROVASI nachgefragt werden, um sicherzustellen, dass die Daten aktuell sind. Aktualisierte Daten werden auf Anfrage bereitgestellt. [Letzte Revision 29.03.2024].

5 jahre garantie

CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spanien

Kontakt
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**