
# QUERCUS 400

IP66 Wandmontierte

ROVASI
Positive Lighting







## 520UND.4-I1104

IP66 | IK07 | 850º | +RAL | 3.69Kg

Wall-mounted fixture with 360º light emission, radial beam.
Cylindrical design with a diameter of 140mm.
Luminaire height: 300mm.
Protection rating against dust and moisture: IP66 – full protection.
Protection rating for resistance against harmful mechanical impacts: IK07.
Die-cast aluminium body and top cover made of die-cast aluminium coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.
5mm fluted clear borosilicate glass.
A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screw.
Silicone gasket.
Anticondensation device.
PCB on the top of the fixture.
Built-in driver included. Ambient temperature: up to 50ºC.
Electronic options for light control: DALI.
Pre-wiring with 25cm of 3x1mm2 cable.
Double cable gland entry for installation in series.
IP68 connector not included, it can be ordered separately: F3.A3 (On/Off) / F3.A5 (DALI) .
Mounting to the wall through mounting plate with two fixing holes. Cable entry from the mounting plate.

**Lichtquelle-Anschlussleistung:** 7.2 W
**Anschlussleistung:** 7.2 W
**Konstantstromquelle:** 350 mA
**Lichtquelle Lichtstrom:** 1140lm
**Leuchten Lichtstrom:** 798lm
**Farbwiedergabeindex:** 80
**Ähnlichste Farbtemperatu:** 4000K
**Farborttoleranz:** MacAdam 4
**Winkel:** 360º
**LOR:** 70%
**Durchschnittliche Betriebsdauer:** 50000h
**Durchschnittliche Betriebsdauer:** 52000h L80B50
**Photobiologische Sicherheit Gruppe:** 1
**Leuchten Lichtausbeute:** 111 lm/W
**Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse** E






| C0 / C90 | d=0 | d=1 | d=2 | d=3 | d=4 |
|---|---|---|---|---|---|
| h=1 | 2.0 / 2.0 | 3.7 / 7.0 | 3.2 / 1.6 | 0.8 / 0.4 | 0.3 / 0.2 |
| h=2 | 0.5 / 0.5 | 0.3 / 0.8 | 0.9 / 1.7 | 1.7 / 0.9 | 0.8 / 0.4 |
| h=3 | 0.2 / 0.2 | 0.2 / 0.2 | 0.1 / 0.7 | 0.4 / 0.8 | 0.9 / 0.5 |
| h=4 | 0.1 / 0.1 | 0.1 / 0.1 | 0.1 / 0.2 | 0.1 / 0.5 | 0.2 / 0.4 |
| h=5 | 0.1 / 0.1 | 0.1 / 0.1 | 0.1 / 0.1 | 0.1 / 0.2 | 0.0 / 0.3 |

**Elektronische Ausrüstung**
**S:** On/Off
**D:** DALI-2
*Ein beliebiges vorgenanntes Suffix **-S, -D** zur Referenz hinzufüge, um die gewünschte elektronische Ausrüstung anzugeben.

**Finishes**
**1:** RAL9010: Reinweiß, **2:** RAL9005: Tiefschwarz, **4:** RAL7016: Anthrazitgrau, **7:** RAL9006: Weißaluminium

**Aufrüstbar, austauschbar, reparierbar**



Anmerkung

Die LED-Technologie und Leistungsdaten sind einem ständigen Wandel unterworfen. Aktuelle Details müssen daher bei ROVASI nachgefragt werden, um sicherzustellen, dass die Daten aktuell sind. Aktualisierte Daten werden auf Anfrage bereitgestellt. [Letzte Revision 29.03.2024].



**5 jahre garantie**

CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

**ROVASI S.L.**
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spanien

**Kontakt**
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**