QUERCUS 400
IP66 Wandmontierte

ROVASI
Positive Lighting




530UND.4-I1172

IP66 | IK07 | 850º | +RAL | 4.41Kg

Wall-mounted fixture with 360º light emission, radial beam.
Cylindrical design with a diameter of 140mm.
Luminaire height: 416mm.
Protection rating against dust and moisture: IP66 – full protection.
Protection rating for resistance against harmful mechanical impacts: IK07.
Die-cast aluminium body and top cover made of die-cast aluminium coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.
5mm fluted clear borosilicate glass.
A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screw.
Silicone gasket.
Anticondensation device.
PCB on the top of the fixture.
Built-in driver included. Ambient temperature: up to 50ºC.
Electronic options for light control: DALI.
Pre-wiring with 25cm of 3x1mm2 cable.
Double cable gland entry for installation in series.
IP68 connector not included, it can be ordered separately: F3.A3 (On/Off) / F3.A5 (DALI) .
Mounting to the wall through mounting plate with two fixing holes. Cable entry from the mounting plate.

Lichtquelle-Anschlussleistung: 7,5 W
Anschlussleistung: 7.5 W
Konstantstromquelle: 350 mA
Lichtquelle Lichtstrom: 774lm
Leuchten Lichtstrom: 635lm
Farbwiedergabeindex: 93
Ähnlichste Farbtemperatu: 2700K
Farborttoleranz: MacAdam 4
Winkel: 360º
LOR: 82%
Durchschnittliche Betriebsdauer: 50000h
Durchschnittliche Betriebsdauer: 52000h L80B50
Photobiologische Sicherheit Gruppe: 1
Leuchten Lichtausbeute: 85 lm/W
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse consult





C0 / C90	d=0	d=1	d=2	d=3	d=4
h=1	1.7 / 1.7	7.1 / 3.6	1.5 / 0.7	0.4 / 0.3	0.2 / 0.1
h=2	0.4 / 0.4	0.3 / 0.9	1.8 / 0.9	0.9 / 0.4	0.4 / 0.2
h=3	0.2 / 0.2	0.1 / 0.2	0.2 / 0.5	0.8 / 0.4	0.5 / 0.2
h=4	0.1 / 0.1	0.1 / 0.1	0.1 / 0.2	0.3 / 0.3	0.4 / 0.2
h=5	0.1 / 0.1	0.1 / 0.1	0.0 / 0.1	0.0 / 0.2	0.2 / 0.2

Elektronische Ausrüstung
S: On/Off
D: DALI-2
*Ein beliebiges vorgenanntes Suffix **-S, -D** zur Referenz hinzufüge, um die gewünschte elektronische Ausrüstung anzugeben.

Finishes
1: RAL9010: Reinweiß, **2:** RAL9005: Tiefschwarz, **4:** RAL7016: Anthrazitgrau, **7:** RAL9006: Weißaluminium

Aufrüstbar, austauschbar, reparierbar





Anmerkung

Die LED-Technologie und Leistungsdaten sind einem ständigen Wandel unterworfen. Aktuelle Details müssen daher bei ROVASI nachgefragt werden, um sicherzustellen, dass die Daten aktuell sind. Aktualisierte Daten werden auf Anfrage bereitgestellt. [Letzte Revision 29.03.2024].

5 jahre garantie

CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spanien

Kontakt
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**