
UNEDO 100

Opal diffuser IP66 Bollards






130UND.4-I1172

IP66 | IK10 | 850º | +RAL | 3.56Kg

Bollard with 360º light emission, radial beam.
Bollard head with a diameter of 140mm.
Bollard height : 300mm.
Protection rating against dust and moisture: IP66 – full protection.
Protection rating for resistance against harmful mechanical impacts: IK10.
Die-cast aluminium body and top cover made of die-cast aluminium and extruded aluminium tube coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.
5mm extruded polycarbonate diffuser made by resins UV stabilized. Opal finish.
A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screw.
Silicone gasket.
Anticondensation device.
PCB on the top of the fixture.
Built-in driver included. Ambient temperature: up to 50ºC.
Electronic options for light control : DALI.
Pre-wiring with 25cm of 3x1mm2 cable.
Double cable gland entry for installation in series.
IP68 connector not included, it can be ordered separately: F3.A3 (On/Off) / F3.A5 (DALI) Mounting base supplied with the fixture.
Accessory for installation in concrete reference F3.P1.BLD
Accessory for installation in grass reference F3.O1.BLD





Lichtquelle-Anschlussleistung: 7.5 W
Anschlussleistung: 7.5 W
Konstantstromquelle: 350 mA
Lichtquelle Lichtstrom: 774lm
Leuchten Lichtstrom: 341lm
Farbwiedergabeindex: 93
Ähnlichste Farbtemperatu: 2700K
Farborttoleranz: MacAdam 4
Winkel: 360º
LOR: 44%
Durchschnittliche Betriebsdauer: 50000h
Durchschnittliche Betriebsdauer: 52000h L80B50
Photobiologische Sicherheit Gruppe: 1
Leuchten Lichtausbeute: 45 lm/W
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse consult

Elektronische Ausrüstung
S: On/Off
D: DALI-2
*Ein beliebiges vorgenanntes Suffix **-S, -D** zur Referenz hinzufüge, um die gewünschte elektronische Ausrüstung anzugeben.

Finishes
1: RAL9010: Reinweiß, **2:** RAL9005: Tiefschwarz, **4:** RAL7016: Anthrazitgrau, **7:** RAL9006: Weißaluminium

Aufrüstbar, austauschbar, reparierbar





Anmerkung

Die LED-Technologie und Leistungsdaten sind einem ständigen Wandel unterworfen. Aktuelle Details müssen daher bei ROVASI nachgefragt werden, um sicherzustellen, dass die Daten aktuell sind. Aktualisierte Daten werden auf Anfrage bereitgestellt. [Letzte Revision 28.03.2024].

5 jahre garantie

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spanien

Kontakt
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**