

# KIBRI 100

# IP20 Recessed linear downlights









## 150KBR.11-I1210











Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 310mm length and in a width of 70mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

White finish modular optics in 7 cells designed to ensure visual comfort. Blind covers available with a length of 280mm or its multiples: accessory reference M5.Y.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.

Ceiling-mounted using steel support with screws. It is possible to combine different lengths and junction modules in different ways to create customized design.

lmax=606 Cd

200

300

400

η=100.0% ▼M ▼Ø ▼LUX

1.63 604

8.1 24

151

1

2 3.3

3 4.9

4 6.5

Light source power: 4.7 W Luminaire connected power: 6.7 W Constant Current: 250 mA

Light source luminous flux: 935lm Luminaire luminous flux: 916lm

**CRI:** 80

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam3

Beam Angle: 78° **LOR:** 98%

Average Service Life: 50000h LED reliability: >90.000h L80B10

**UGR:** <19

Photobiological safety group: 1 Luminaire efficiency: 137 lm/W

This product contains a light source of energy efficiency class B

#### **Electronic Equipment**

**D:** DALI-2/switchDIM/corridorFUNCTION

\*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

#### **Finishes**

11: White frame - white reflector

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 27.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### **ROVASIS.L.**

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com