

# MINI QUID Small recessed downlights









## 101MQD.1-R680



IP20 850°











lmax=841 Cd

300

600



η=100.0% ▼ M ▼ Ø ▼LUX

1.72 841

3.4 210

8.6

1

3 5.2

4 6.9 53

82°

Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.

Circular design in diameter 110mm.

Sandblasted metalized aluminium reflector.

Powder painted die-cast aluminium trim available in assorted finishes.

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0110].

Remote driver supplied. Electronic options for lighting control: DALI/DSI. Passive temperature management: heat dissipation flows through heat sink.

Ceiling-mounted using galvanised steel support with spring clamps.

Fixture power: 11.8 W Constant Current: 350 mA

Luminous flux of the light source: 1850lm Luminous flux of the fixture: 1319lm

**CRI:** >80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam3

Beam Angle: 82°

**LOR:** 71%

Average Service Life: 50000h LED reliability: 51000h L80B10

**UGR:** >21 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 1m

Photobiological safety group: 1

**Cd/Klm:** 638

Luminous efficacy: 112 lm/W

Imax: 842 Cd

This product contains a light source of energy efficiency class A++

### **Electronic Equipment**

**D:** DALI-2/DSI switchDIM/corridorFUNCTION

\*Add the suffix **-D** after the reference to indicate your electronic equipment choice.

#### **Finishes**

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 19.04.2024]

5 years guarantee



Spain