

# MINI QUID Small recessed downlights









## 101MQD.1-R681



IP20 850°











lmax=878 Cd

300

450

600





η=100.0% ▼ M ▼ Ø ▼LUX

1

3 5.2

4 6.9 55

1.72 878

3.4 219

8.6 35 82°

Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.

Circular design in diameter 110mm.

Sandblasted metalized aluminium reflector.

Powder painted die-cast aluminium trim available in assorted finishes.

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0110].

Remote driver supplied. Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through heat sink.

Ceiling-mounted using galvanised steel support with spring clamps.

Luminaire connected power: 11.8 W Constant Current: 350 mA Light source luminous flux: 1930lm Luminaire luminous flux: 1376lm **CRI:** >80

Colour Temperature: 4000K Chromaticity Tolerance: MacAdam3

Beam Angle: 82°

**LOR:** 71%

Average Service Life: 50000h LED reliability: 51000h L80B10

**UGR:** >21 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 1m

Photobiological safety group: 1

Cd/Klm: 638

Luminaire efficiency: 117 lm/W

Imax: 878 Cd

This product contains a light source of energy efficiency class A++

### **Electronic Equipment**

D: DALI-2/switchDIM/corridorFUNCTION

\*Add the suffix -D after the reference to indicate your electronic equipment choice.

#### **Finishes**

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee



Spain