

MINI QUID Small recessed downlights









101MQD.1-R682



IP20 850°











Imax=1164 Cd

400

600

800

1000



η=100.0% ▼ M ▼ Ø ▼LUX

1

3 5.2

4 6.9 73

1.72 1164

8.6 47

291

82°

Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.

Circular design in diameter 110mm.

Sandblasted metalized aluminium reflector.

Powder painted die-cast aluminium trim available in assorted finishes.

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0110].

Remote driver supplied. Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through heat sink.

Ceiling-mounted using galvanised steel support with spring clamps.

Luminaire connected power: 17.3 W Constant Current: 500 mA Light source luminous flux: 2560lm Luminaire luminous flux: 1825lm **CRI:** >80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam3

Beam Angle: 82°

LOR: 71%

Average Service Life: 50000h LED reliability: 48000h L80B10

UGR: >21 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 1m

Photobiological safety group: 1

Cd/Klm: 638

Luminaire efficiency: 105 lm/W

Imax: 1164 Cd

This product contains a light source of energy efficiency class A++

Electronic Equipment

D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -D after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13