TUNABLE WHITE


Special Applications







559



104CND.1.02-I720



IP20 850°











Recessed ceiling mounted downlights with symmetrical light distribution to achieve an effective ambient

Flush installation, the fixture is completely fitted in the ceiling void. Installation in plasterboard ceilings. Circular design available in 559mm diameter.

Powder painted one piece aluminium profile available in assorted finishes, customized RAL under request.

Polycarbonate opal diffuser (thickness 3mm.).

Tridonic high energy efficiency printed circuit board. Tunable White PCB: 3000K - 6000K Built-in driver, included.

Electronic options for lighting control: SwitchDIM/ColourSwitch/DALI-2.

3 hours battery available as option.

Passive temperature management: heat dissipation flows through the fixture body itself. Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 30mm. CANDRA can be combined with PLACE pendant downlights and LEDA surface-mounted downlights to get a harmonious finish.

Light source power: 28 W

Luminaire connected power: 28 W

Constant Current: 125 mA

Light source luminous flux: 4650lm

CRI: >90

Colour Temperature: 2700K-6500K Chromaticity Tolerance: MacAdam 3 Average Service Life: 50000h LED reliability: 50000h L90B50 Photobiological safety group: 1

This product contains a light source of energy effic

Electronic Equipment

T: DALI-2/switchDIM/ColourSwitch

*Add the suffix -T after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee



Spain

T. +34 93 881 35 12 T. +34 93 881 37 13

Contact