# TUNABLE WHITE


## Special Applications







841



### 105CND.1.02-I721



IP20 850°











Recessed ceiling mounted downlights with symmetrical light distribution to achieve an effective ambient lighting.

Flush installation, the fixture is completely fitted in the ceiling void. Installation in plasterboard ceilings. Circular design available in 841mm diameter.

Powder painted one piece aluminium profile available in assorted finishes, customized RAL under request.

Polycarbonate opal diffuser (thickness 3mm.).

Tridonic high energy efficiency printed circuit board. Tunable White PCB: 3000K - 6000K Built-in driver, included.

Electronic options for lighting control: SwitchDIM/ColourSwitch/DALI/DSI.

3 hours battery available as option.

Passive temperature management: heat dissipation flows through the fixture body itself. Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 30mm. CANDRA can be combined with PLACE pendant downlights and LEDA surface-mounted downlights to get a harmonious finish.

Light source power: 58 W Fixture power: 58 W Constant Current: 250 mA

Luminous flux of the light source: 9610lm

**CRI:** >90

Colour Temperature: 2700K-6500K Chromaticity Tolerance: MacAdam 3 Average Service Life: 50000h LED reliability: 50000h L90B50 Photobiological safety group: 1

This product contains a light source of energy effic

#### **Electronic Equipment**

T: DALI-2/DSI SwitchDIM/ColourSwitch

\*Add the suffix -T after the reference to indicate your electronic equipment choice.

#### **Finishes**

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 19.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346 BSI Cert ISO 14001:2015 - n°EMS 554685

#### **ROVASIS.L.**

T. +34 93 881 35 12 in T. +34 93 881 37 13 w