




110KUU.1.02-I1058



Recessed ceiling mounted downlights with symmetrical light distribution to achieve an effective ambient lighting.
Circular design available in 880mm diameter.
Powder painted aluminium trim available in assorted finishes, customized RAL under request.
PMMA opal diffuser (thickness 3mm).
Tridonic high energy efficiency printed circuit board.
Built-in driver, included.
Electronic options for lighting control: DALI/DSI.
3 hours battery available as option.
Passive temperature management: heat dissipation flows through the fixture body itself.
Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 30mm.
KUU can be combined with PLACE pendant downlights and LEDA surface-mounted downlights to get a harmonious finish.



Light source power: 47 W
Fixture power: 51.32 W
Constant Current: 400 mA
Luminous flux of the light source: 9555lm
Luminous flux of the fixture: 8506lm
CRI: >80
Colour Temperature: 4000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 108°
LOR: 89%
Average Service Life: 50000h
LED reliability: L90B10 >50000h
UGR: <19 under the below indicated parameters
Room dimensions X=4H/8H
Reflectance 20% | 50% | 70%
Luminaire spacing = 0.35m
Photobiological safety group: 1
Luminous efficacy: 166 lm/W
This product contains a light source of energy efficiency class C



Electronic Equipment

S: On/Off
SE: On/Off + 3h battery
D: DALI-2/DSI switchDIM/corridorFUNCTION
DE: DALI/DSI switchDIM+ 3 hours battery
DDE: DALI/DSI switchDIM+ 3 hours battery (DALI)

*Add the suffix **-S, -SE, -D, -DE, -DDE** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 20.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com