

108PLC.1.02-I637



Pendant downlights with symmetrical light distribution to achieve an effective ambient lighting.  
Circular design available in 350mm diameter.  
Powder painted one piece aluminium profile available in assorted finishes, customized RAL under request.  
PMMA opal diffuser (thickness 3mm.).  
High energy efficiency printed circuit board.  
Built-in driver, included.  
Electronic options for lighting control: DALI-2.  
Passive temperature management: heat dissipation flows through the fixture body itself.  
Ceiling-mounted using ceiling rose. Suspended 1 meter by four steel cords. Transparent electronic wire.  
PLACE can be combined with KUJ and CANDRA recessed downlights and LEDA surface-mounted downlights to get a harmonious finish.

**Light source power:** 17 W  
**Luminaire connected power:** 18.14 W  
**Constant Current:** 600 mA  
**Light source luminous flux:** 2600lm  
**Luminaire luminous flux:** 2262lm  
**CRI:** >80  
**Colour Temperature:** 3000K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 114°  
**LOR:** 87%

**Average Service Life:** 50000h  
**LED reliability:** >50000 L90B10  
**UGR:** <19 under the below indicated parameters  
Room dimensions X=4H/8H  
Reflectance 20% | 50% | 70%  
Luminaire spacing = 1m

**Photobiological safety group:** 1  
**Cd/Klm:** 345  
**Luminaire efficiency:** 125 lm/W  
**Imax:** 780 Cd

**This product contains a light source of energy efficiency class C**


**Electronic Equipment**

**S:** On/Off  
**D:** DALI-2/switchDIM/corridorFUNCTION


\*Add the suffix **-S, -D** after the reference to indicate your electronic equipment choice.

**Finishes**

**2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White



**Upgradeable, Replaceable, Repairable**



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 25.04.2024]

**5 years guarantee**



BSI Cert ISO 9001:2015 - n°FM 39346  
BSI Cert ISO 14001:2015 - n°EMS 554685

**ROVASI S.L.**  
Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

**Contact**  
T. +34 93 881 35 12    info@rovasi.com  
T. +34 93 881 37 13    **www.rovasi.com**