


101SHW.1-R863



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.
Circular design in diameter 150mm
Remarkable low height: 50mm.
Sandblasted metalized aluminium reflector.
Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request.
Drop glass disk accessory available in assorted colours [reference M1.A0150].
Drop metal disk accessory available in assorted colours [reference M1.B0150].
Decorative LED ring accessory available in assorted colours [reference F1.B0150].
Glass accessory available to increase the protection rating to IP54 | IK05 from underneath [reference M2.B0150].
316L stainless steel trim accessory with flush glass and silicone rubber gasket to increase the protection rating to IP65 | IK07 from underneath [reference M2.C0150].
Remote driver supplied.
Electronic options for lighting control: DALI-2.
3 hours battery available as option (class I).
Passive temperature management: heat dissipation flows through an aluminium aluminium heat sink diffuser.
Ceiling-mounted using spring clamps.

Light source power: 11 W
Fixture power: 12.61 W
Constant Current: 350 mA
Luminous flux of the light source: 1960lm
Luminous flux of the fixture: 1646lm
CRI: >80
Colour Temperature: 2700K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 105°
LOR: 84%
Average Service Life: 50000h
LED reliability: 50000h L90B10
UGR: <19 under the below indicated parameters
Room dimensions X=4H/8H
Reflectance 20% | 50% | 70%
Luminaire spacing = 0.6m
Photobiological safety group: 1
Cd/Klm: 387
Luminous efficacy: 131 lm/W
Imax: 759 Cd
This product contains a light source of energy efficiency class D



Electronic Equipment


K: On/Off (basic)
S: On/Off (AC/DC + looping through)
SE: On/Off (AC/DC+looping) + 3h battery
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM/corridorFUNCTION + Battery 3h
B: Bluetooth-Casambi

*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 25.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarrà
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com