Minidownlights



η=100.0% ▼ M ▼ Ø ▼LUX

1

3 2.3

4

0.76 737


1.52 184


3.0 46

3.8

42°







103TNS.1-R938



IP20













lmax=737 Cd

400

500

600

Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or ambient lighting.

Round design in diameter 55mm.

Aluminium trim powder painted in various finishes, customized RAL under request.

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0035].

Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0035].

Remote driver included.

Passive temperature management: heat dissipation via aluminium heat sink.

Ceiling-mounted using galvanised steel support with spring clamps.

Light source power: 4.9 W Fixture power: 5.45 W Constant Current: 150 mA

Luminous flux of the light source: 690lm Luminous flux of the fixture: 435lm

CRI: >90

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 42°

LOR: 63%

Average Service Life: 50000h LED reliability: >53000h L80B50

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.6m

Photobiological safety group: 1

Cd/Klm: 1694

Luminous efficacy: 80 lm/W

Electronic Equipment

S: On/Off SE: On/Off + 3h battery D: DALI-2/ DSI/ switchDIM DE: DALI-2/DSI switchDIM + 3h battery

*Add the suffix -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 17.04.2024]

5 years guarantee



Spain