



101TSS.1-R937



Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or ambient lighting.
Square design in 60mm x 60mm.
Body powder painted in various finishes, customized RAL under request.
Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0035].
Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0035].
Remote driver included.
Electronic options for lighting control: DALI-2.
3 hours battery available as option*.
Passive temperature management: heat dissipation via aluminium heat sink.
Ceiling-mounted using galvanised steel support with spring clamps.

Light source power: 4.9 W
Luminaire connected power: 5.45 W
Constant Current: 150 mA
Light source luminous flux: 660lm
Luminaire luminous flux: 449lm
CRI: >90
Colour Temperature: 2700K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 17°
LOR: 68%

Average Service Life: 50000h
LED reliability: >53000h L80B50
UGR: <19 under the below indicated parameters
Room dimensions X=4H/8H
Reflectance 20% | 50% | 70%
Luminaire spacing = 0.45m

Photobiological safety group: 1
Cd/Klm: 5192
Luminaire efficiency: 82 lm/W

This product contains a light source of energy efficiency class E


Electronic Equipment

K: On/Off (basic)
S: On/Off (AC/DC)
SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM + 3h battery
B: Bluetooth-Casambi


*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com