
# TRIANGLE

## Recessed downlights



















lmax=683 Cd

300

400

500

η=100.0% ▼M ▼Ø ▼LUX

1 1.73 683

2

3 5.2

4 6.9 43

5 8.6 27

171 3.5

Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or general lighting.

Triangular design in 216mm side.

Protection rating against dust and moisture: IP54 from underneath.

High-purity matt anodised aluminium reflector.


Powder painted aluminium frame available in assorted finishes, customized RAL under request.

Frosted protection glass. Remote driver included.

Electronic options for lighting control: DALI/DSI.

3 hours battery available as option (class I).

Passive temperature management: heat dissipation flows through an aluminium heat sink. Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 30mm.



Luminous flux of the light source: 2125lm Luminous flux of the fixture: 1190lm

**CRI:** >80

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 82° **LOR:** 56%

Average Service Life: 50000h LED reliability: 50000h L90B10

**UGR:** >22

Photobiological safety group: 1 Luminous efficacy: 94 lm/W

This product contains a light source of energy efficiency class D



216



#### **Electronic Equipment**

K: On/Off (basic) N: On/Off (AC/DC + looping through)
SE: On/Off (AC/DC + looping) + 3h battery
D: DALI-2/DSI switchDIM/corridorFUNCTION
DE: DALI-2/DSI switchDIM/corridorFUNCTION + Battery 3h

\*Add the suffix -K, -S, -SE, -D, -DE after the reference to indicate your electronic equipment choice.

#### **Finishes**

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 19.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### **ROVASI S.L.**

Spain

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13