




## 102BXS.1-R939



Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or ambient lighting.  
 Round design with trimless appearance in diameter 72mm.  
 Aluminium body and interior circle powder painted in various finishes, customized RAL under request.  
 To complete the effect of this luminaire, it is suggested that the circle be painted the same RAL colour as the ceiling.  
 Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0035].  
 Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0035].  
 Remote driver included.  
 Electronic options for lighting control: DALI-2.  
 3 hours battery available as option\*.  
 Passive temperature management: heat dissipation via aluminium heat sink.  
 Ceiling-mounted using galvanised steel support with spring clamps.

**Light source power:** 4.9 W  
**Luminaire connected power:** 5.45 W  
**Constant Current:** 150 mA  
**Light source luminous flux:** 735lm  
**Luminaire luminous flux:** 515lm  
**CRI:** >90  
**Colour Temperature:** 4000K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 28°  
**LOR:** 70%

**Average Service Life:** 50000h  
**LED reliability:** >53000h L80150  
**UGR:** <19 under the below indicated parameters  
 Room dimensions X=4H/8H  
 Reflectance 20% | 50% | 70%  
 Luminaire spacing = 0.6m  
**Photobiological safety group:** 1  
**Cd/Klm:** 2910  
**Luminaire efficiency:** 94 lm/W  
**This product contains a light source of energy efficiency class E**

**Electronic Equipment**

**K:** On/Off (basic)  
**S:** On/Off (AC/DC)  
**SE:** On/Off (AC/DC) + Battery 3h  
**D:** DALI-2/switchDIM/corridorFUNCTION  
**DE:** DALI-2/switchDIM + 3h battery  
**B:** Bluetooth-Casambi

\*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

**Finishes**

**2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

**Upgradeable, Replaceable, Repairable****Note**

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 25.04.2024]

**5 years guarantee**

BSI Cert ISO 9001:2015 - n°FM 39346  
 BSI Cert ISO 14001:2015 - n°EMS 554685

**ROVASI S.L.**

Ronda de la Font Grossa, 15  
 Pol. Ind. La Gavarra  
 08540 Centelles | Barcelona  
 Spain

**Contact**

T. +34 93 881 35 12 info@rovasi.com  
 T. +34 93 881 37 13 [www.rovasi.com](http://www.rovasi.com)