

# **QUADRATIC SHALLOW**



Recessed downlights








### 101QSH.1-R870



general lighting. Square design available in 225mm x 225mm. Remarkable low height: 64mm. Protection rating against dust and moisture: IP54 from underneath. High-purity matt anodised aluminium reflector. Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request. Sandblasted flush glass diffuser. Remote driver included. Electronic options for lighting control: DALI/DSI. 3 hours battery available as option (class I). Passive temperature management: heat dissipation through heat sink diffuser. Ceiling-mounted using galvanised steel support with spring clamps.

Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or

Light source power: 17 W Fixture power: 18.33 W Constant Current: 500 mA Luminous flux of the light source: 2870lm Luminous flux of the fixture: 1952lm **CRI:** >80 Colour Temperature: 3000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 86° LOR: 68% Average Service Life: 50000h LED reliability: 50000h L90B10 UGR: <22 Photobiological safety group: 1 Cd/Klm: 487 Luminous efficacy: 106 lm/W



Imax: 951 Cd This product contains a light source of energy efficiency class D

#### **Electronic Equipment**

K: On/Off (basic) S: On/Off (AC/DC + looping through) SE: On/Off (AC/DC + looping) + 3h battery D: DALI-2/DSI switchDIM/corridorFUNCTION DE: DALI-2/DSI switchDIM/corridorFUNCTION + Battery 3h

\*Add the suffix -K, -S, -SE, -D, -DE after the reference to indicate your electronic equipment choice.

#### Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 16.04.2024]

## 5 years guarantee **CE** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### ROVASI S.L.

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra

08540 Centelles | Barcelona

#### Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com