

QUADRATIC SHALLOW

Recessed downlights










101QSH.1-R882







Imax=1345 Cd

750





η=100.0% ▼ M ▼ Ø ▼LUX

1

3

4 7.4

1.86 1345

84

3.7 336

9.3

86°

Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or general lighting.

Square design available in 225mm x 225mm.

Remarkable low height: 89mm.

Protection rating against dust and moisture: IP54 from underneath.

High-purity matt anodised aluminium reflector.

Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request.

Sandblasted flush glass diffuser.

Remote driver included.

Electronic options for lighting control: DALI-2. 3 hours battery available as option (class I).

Passive temperature management: heat dissipation through heat sink diffuser.

Ceiling-mounted using galvanised steel support with spring clamps.

Light source power: 23 W Luminaire connected power: 25.33 W

Constant Current: 700 mA Light source luminous flux: 4060lm Luminaire luminous flux: 2761lm

CRI: >80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 86°

LOR: 68%

Average Service Life: 50000h LED reliability: 50000h L90B10

UGR: >22

Photobiological safety group: 1

Cd/Klm: 487

Luminaire efficiency: 109 lm/W

Imax: 1345 Cd

This product contains a light source of energy efficiency class D

Electronic Equipment

K: On/Off (basic)
S: On/Off (AC/DC + looping through)

D: DALI-2/switchDIM/corridorFUNCTION

DE: DALI-2/switchDIM/corridorFUNCTION

DE: DALI-2/switchDIM/corridorFUNCTION + Battery 3h

*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASI S.L.**

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Contact

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13