



102TER.8.01-I863



Recessed buried uplight with symmetrical light distribution.
Circular design in diameter: 180mm.
IP68 protection rating that enables it to resist immersion to a depth of 1m.
Protection rating of resistance to harmful mechanical impacts: IK10.
Load supported: 7100 Kg. It can be driven over by vehicles with pneumatic tyres.
Robust and corrosion-resistant black painted aluminium housing with C5-M special coating for environments with very high corrosivity. 316L stainless steel marine grade trim.
Aluminium reflector in assorted finishes: faceted metalized or sandblasted metalized depending on the beam angle outcome.
Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0111].
15 mm tempered protection glass clear as standard, other finishes under request.
Temperature resistant silicone rubber gasket.
A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screws [reference F2.A0180+F2.A1].
Built-in driver, included.
Electronic options for lighting control: DALI-2.
The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.
Passive temperature management: heat dissipation flows through the fixture body itself.
Ground mounted by two fixing holes.
Supplied with aluminium insertion tube as standard. Insertion tube for flush installation as accessory [reference M3.C0180].
Double cable gland entry for installation in series.
Pre-wiring of 0.5 metres cable 3x1mm².
IP68 connector to be ordered separately [reference F3.A3 (On/Off) / F3.A5 (DALI)].

Luminaire luminous flux: 1607lm
Luminaire connected power: 12.61 W
Luminaire efficiency: 127 lm/W
Light source luminous flux: 1960lm
Light source power: 11 W
Constant Current: 350 mA
CRI: >80
Colour Temperature: 2700K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 12°
LOR: 82%
LED reliability at nominal Ta = 25°C: 50000h L90B10
Photobiological safety group: 1
Cd/Klm: 8183
Imax: 16039 Cd
This product contains a light source of energy efficiency class D



Electronic Equipment


S: On/Off (AC/DC)
D: DALI-2/switchDIM/corridorFUNCTION
B: Bluetooth-Casambi [8m]

*Add the suffix **-S**, **-D**, **-B** after the reference to indicate your electronic equipment choice.

Finishes

8: Stainless Steel 316L: Marine grade, **1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 03.07.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com