

LENTIE

IP65 Wall mounted fixtures

ROVASI
Positive Lighting








101LNT.1.01-I871

IP65 | IK10 | 850º | +ELEC | +INSTAL | +RAL | 6.85Kg

Surface mounted fixtures with symmetrical light distribution. Wall fixtures with light emission on two sides.
Cylindrical design in 265mm diameter.
Protection rating against dust and moisture: entire IP65.
Protection rating for resistance to harmful mechanical impacts: IK10.
Robust body made of die-cast aluminium and trim coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.
Sandblasted metalized aluminium reflector.
Impact resistant cover made of clear polycarbonate (IK10).
Optional clear glass diffuser (IK05). Frosted or painted diffuser finishes under request.
Temperature resistant silicone rubber gasket.
Two anti-condensation device.
A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screws [reference 2 x F2.A0265 + F2.01].
Built-in driver, included.
Passive temperature management: heat dissipation flows through the fixture body itself.
Mounting to the wall through mounting plate with two fixing holes.
Two cable entry from the fixation plate.

Light source power: 2x 17 W
Fixture power: 36.66 W
Constant Current: 500 mA
Luminous flux of the light source: 2x 2990lm
Luminous flux of the fixture: 2x1884lm
CRI: >80
Colour Temperature: 4000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 102º
LOR: 63%
Average Service Life: 50000h
LED reliability: 50000h L90B10
Photobiological safety group: 1
Cd/Klm: 295
Luminous efficacy: 51 lm/W
This product contains a light source of energy efficiency class D



▼M	▼Ø	▼LUX
1	2.5	1459
2	4.9	365
3	7.4	162
4	9.9	91
5	12.3	58


Electronic Equipment


S: On/Off
D: DALI-2/DSI/switchDIM
There are accessories available for dimming devices.
*Add the suffix **-S, -D** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White textured, **2:** RAL9005: Jet Black textured, **4:** RAL7016: Anthracite Grey textured, **7:** RAL9006: White Aluminium textured

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 29.03.2024]

5 years guarantee

EAC CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**