

KERI
Pendant downlights

ROVASI
Positive Lighting








107KER.1-I908

IP20 | 850º | +ELEC | +INSTAL | +RAL | 1.85Kg

Pendant downlights with symmetrical light distribution to achieve an effective task or general lighting.
Neutral cylindrical body in diameter 80mm.
Sandblasted metalized aluminium reflector silver finished.
Powder painted aluminium profile available in assorted finishes, customized RAL under request.
Built-in driver, included.
Electronic options for lighting control: DALI/DSI.
Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself.
Delivered with 1 meter steel cord as standard. Transparent electronic wire. Mounted to the ceiling by cylindrical ceiling rose.
For a more dynamic result, it can be supplied with an adapter for three-phase track [reference M3.A].
KERI can be combined with the GOTA surface mounted downlights line fixtures to get a harmonious finish.

Light source power: 4.8 W
Fixture power: 5.32 W
Constant Current: 150 mA
Luminous flux of the light source: 690lm
Luminous flux of the fixture: 428lm
CRI: >90
Colour Temperature: 2700K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 38º
LOR: 62%
Average Service Life: 50000h
LED reliability: 56000h L80B10
UGR: 16
Photobiological safety group: 1
Cd/Klm: 1077
Luminous efficacy: 80 lm/W
Imax: 743 Cd
This product contains a light source of energy efficiency class E





▼M	▼Ø	▼LUX	38°
1	0.69	743	
2	1.37	186	
3	2.1	83	
4	2.7	46	
5	3.4	30	

Electronic Equipment
S: On/Off
D: DALI-2/DSI/switchDIM
There are accessories available for dimming devices.
*Add the suffix **-S, -D** after the reference to indicate your electronic equipment choice.

Finishes
1: RAL9010: Pure White textured, **2:** RAL9005: Jet Black textured, **4:** RAL7016: Anthracite Grey textured, **7:** RAL9006: White Aluminium textured

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 29.03.2024]

5 years guarantee

EAC CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**