

HELIX

Pendant downlights

ROVASI
Positive Lighting








101HEX.1-I882

IP20 | 850º | +DECO | +ELEC | +INSTAL | +RAL | 4.3Kg

Pendant downlight with symmetrical light distribution to achieve an effective task or ambient lighting.




▼M	▼Ø	▼LUX	53°
1	1.00	3831	
2	2.0	958	
3	3.0	426	
4	4.0	239	
5	5.0	153	


Light source power: 23 W
Fixture power: 25.33 W
Constant Current: 700 mA
Luminous flux of the light source: 4060lm
Luminous flux of the fixture: 3086lm
CRI: >80
Colour Temperature: 3000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 53º
LOR: 76%
Average Service Life: 50000h
LED reliability: 50000h L90B10
UGR: <16
Photobiological safety group: 1
Cd/Klm: 944
Luminous efficacy: 122 lm/W
Imax: 3833 Cd
This product contains a light source of energy efficiency class D

Electronic Equipment
S: On/Off
D: DALI-2/DSI/switchDIM
There are accessories available for dimming devices.
*Add the suffix **-S, -D** after the reference to indicate your electronic equipment choice.

Finishes
1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 28.03.2024]

5 years guarantee

EAC CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**