

ROCKET

Wall mounted fixtures









107RCK.1-I910









Wall mounted luminaries with symmetrical light distribution to achieve an effective task or general lighting. Neutral cylindrical body in diameter 80mm.

Sandblasted metalized aluminium reflector silver finished.

Powder painted aluminium profile available in assorted finishes, customized RAL under request.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture

Wall mounted by aluminium mounting plate with two fixing points. Cable entry through the aluminium wall mounting plate.

ROCKET can be combined with the KERI pendant line and the GOTA surface mounted fixtures to get a harmonious finish.

max=846 Cd

η=62.2% ▼ M ▼ Ø ▼LUX

2

3 2.1

4 2.7

0.69

1.37 211

> 3.4 34

Luminaire connected power: 4.8 W

Constant Current: 150 mA Light source luminous flux: 785lm Luminaire luminous flux: 487lm

CRI: >90

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 38° **LOR:** 62%

Average Service Life: 50000h LED reliability: 56000h L80B10 Photobiological safety group: 1

Cd/Klm: 1077

Luminaire efficiency: 101 lm/W

Imax: 845 Cd

This product contains a light source of energy efficiency class A++

Electronic Equipment

D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix **-D** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 27.04.2024]



Spain

T. +34 93 881 37 13