


ROCKET Wall mounted fixtures







108RCK.1-I910



Wall mounted luminaries with symmetrical light distribution to achieve an effective task or general lighting. Neutral cylindrical body in diameter 80mm.

Sandblasted metalized aluminium reflector silver finished.

Powder painted aluminium profile available in assorted finishes, customized RAL under request.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself.

Wall mounted by aluminium mounting plate with two fixing points. Cable entry through the aluminium wall mounting plate.

ROCKET can be combined with the KERI pendant line and the GOTA surface mounted fixtures to get a harmonious finish.

Luminaire connected power: 4.8 W Constant Current: 150 mA Light source luminous flux: 785lm Luminaire luminous flux: 487lm **CRI:** >90 Colour Temperature: 4000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 38° LOR: 62% Average Service Life: 50000h LED reliability: 56000h L80B10

Photobiological safety group: 1 Cd/Klm: 1077 Luminaire efficiency: 101 lm/W

Imax: 845 Cd This product contains a light source of energy efficiency class A++

Electronic Equipment

D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -D after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

T. +34 93 881 35 12 T. +34 93 881 37 13

Contact

info@rovasi.com www.rovasi.com

max=846 Cd η=62.2% ▼M ▼Ø ▼LUX 38° 0.69 1 846 1.37 211 2 3 2.1 94 45 4 2.7 53 5 3.4 34