

# **PRISMA**

## Surface mounted downlights









### 101PSM.1-I865



IP20 850°



Surface-mounted downlight with symmetrical light distribution to achieve an effective task or ambient

Neutral cubic body in dimensions 225mm x 225mm.

High purity matt anodised aluminium reflector.

Powder painted aluminium body available in assorted finishes, customized RAL under request.

Flush decorative glass available as accessory.

Drop glass accessory available in assorted colours [reference M1.C0225].

Drop metal square accessory available in assorted colours [reference M1.E0225].].

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture

Imax=1454 Cd

500

750

1000

η=82.5% ▼ M ▼ Ø ▼LUX

1.45 1454

7.3 58

91

1

2 2.9 364

3

4 5.8 72°

Mounting to the ceiling plate with two securing points. Cable entry from the top of the fixture.

Light source power: 11 W Fixture power: 12.61 W Constant Current: 350 mA

Luminous flux of the light source: 2125lm Luminous flux of the fixture: 1743lm

**CRI:** >80

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 72°

**LOR:** 82%

Average Service Life: 50000h LED reliability: 50000h L90B10

**UGR:** <19

Photobiological safety group: 1

Cd/Klm: 684

Luminous efficacy: 138 lm/W

**Imax:** 1454 Cd

This product contains a light source of energy efficiency class D

#### **Electronic Equipment**

S: On/Off
D: DALI-2/switchDIM/corridorFUNCTION

\*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 24.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### **ROVASIS.L.**

Spain

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com