

PRISMA

Surface mounted downlights









101PSM.1-I867







Surface-mounted downlight with symmetrical light distribution to achieve an effective task or ambient

Neutral cubic body in dimensions 225mm x 225mm.

High purity matt anodised aluminium reflector.

Powder painted aluminium body available in assorted finishes, customized RAL under request.

Flush decorative glass available as accessory.

Drop glass accessory available in assorted colours [reference M1.C0225].

Drop metal square accessory available in assorted colours [reference M1.E0225].].

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture

Imax=1184 Cd

600

η=82.5% ▼ M ▼ Ø ▼LUX

1.45 1184

74 5.8

47 7.3

1

2 2.9 296

3

4

72°

Mounting to the ceiling plate with two securing points. Cable entry from the top of the fixture.

Light source power: 11 W Luminaire connected power: 12.61 W

Constant Current: 350 mA Light source luminous flux: 1730lm Luminaire luminous flux: 1419lm

CRI: >90

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 72° **LOR:** 82%

Average Service Life: 50000h LED reliability: 50000h L90B10

UGR: <19

Photobiological safety group: 1

Cd/Klm: 684

Luminaire efficiency: 113 lm/W

Imax: 1183 Cd

This product contains a light source of energy efficiency class E

Electronic Equipment

S: On/Off
D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASIS.L.

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13