

MILVUM
Decorative Lighting


ROVASI
Positive Lighting







101MLV.1-R913




Semi-recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective ambient lighting.
Blown glass cone available in assorted finishes, customized colour under request.
Protection rating against dust and moisture: IP54 from underneath.
Clear glass fixture screwed into an aluminium body sealed with a silicone trim.
Remote driver supplied.
Electronic standard options for lighting control: DALI/DSI.
Emergency kit as option.
Passive temperature management: heat dissipation flows through an aluminium heat sink.
Ceiling-mounted with spring clamps for easy installation, ceiling thicknesses up to.mm.


Fixture power: 6.5 W
Constant Current: 200 mA
Luminous flux of the light source: 1195lm
CRI: >80
Colour Temperature: 4000K
Chromaticity Tolerance: MacAdam 3
Average Service Life: 50000h
LED reliability: 55000h L80B10
Photobiological safety group: 0
This product contains a light source of energy effic

Electronic Equipment
S: On/Off
D: DALI-2/DSI/switchDIM
There are accessories available for dimming devices.
*Add the suffix **-S, -D** after the reference to indicate your electronic equipment choice.

Finishes
1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 28.03.2024]

5 years guarantee

EAC CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**