


## 101MLV.1-R919



Semi-recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective ambient lighting.

Blown glass cone available in assorted finishes, customized colour under request.

Protection rating against dust and moisture: IP54 from underneath.

Clear glass fixture screwed into an aluminium body sealed with a silicone trim.

Remote driver supplied.

Electronic standard options for lighting control: DALI/DSI.

Emergency kit as option.

Passive temperature management: heat dissipation flows through an aluminium heat sink.

Ceiling-mounted with spring clamps for easy installation, ceiling thicknesses up to .mm.

**Fixture power:** 8.2 W

**Constant Current:** 250 mA

**Luminous flux of the light source:** 1480lm

**CRI:** >80

**Colour Temperature:** 4000K

**Chromaticity Tolerance:** MacAdam 3

**Average Service Life:** 50000h

**LED reliability:** 54000h L80B10

**Photobiological safety group:** 0

**This product contains a light source of energy effic**

### Electronic Equipment

**D:** DALI-2/DSI switchDIM/corridorFUNCTION

\*Add the suffix **-D** after the reference to indicate your electronic equipment choice.

### Finishes

**1:** RAL9010: Pure White

### Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 20.04.2024]

**5 years guarantee**



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

### ROVASI S.L.

Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

### Contact

T. +34 93 881 35 12 info@rovasi.com  
T. +34 93 881 37 13 **www.rovasi.com**