

QUID
Recessed downlights


ROVASI
Positive Lighting








101QID.1-R870



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.
Circular design in diameter 150mm.
Sandblasted metalized aluminium reflector.
Powder painted die-cast aluminium trim available in assorted finishes.
Glass accessory available to increase the protection rating to IP54 from underneath[reference M2.K0150].
Remote driver supplied. Electronic options for lighting control: DALI/DSI.
Passive temperature management: heat dissipation flows through aluminium heat sink.
Ceiling-mounted using galvanised steel support with spring clamps.

Light source power: 17 W
Fixture power: 18.33 W
Constant Current: 500 mA
Luminous flux of the light source: 2870lm
Luminous flux of the fixture: 2124lm
CRI: >80
Colour Temperature: 3000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 50º
LOR: 74%
Average Service Life: 50000h
LED reliability: 50000h L90B10
UGR: <19
Photobiological safety group: 1
Cd/Klm: 1042
Luminous efficacy: 116 lm/W
Imax: 2991 Cd
This product contains a light source of energy efficiency class D




▼M	▼Ø	▼LUX
1	0.93	2992
2	1.87	748
3	2.8	332
4	3.7	187
5	4.7	120

50°

Electronic Equipment
K: On/Off
D: DALI·2/DSI/switchDIM/corridorFUNCTION
B: Bluetooth-Casambi
*Add the suffix **-K, -D, -B** after the reference to indicate your electronic equipment choice.

Finishes
1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 29.03.2024]

5 years guarantee

CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**