# MINI QUID

## Small recessed downlights



η=100.0% ▼ M ▼ Ø ▼LUX

1 1.72 894

3 5.2

4

82°


224

6.9 56

8.6







### 101MQD.1-R924













lmax=894 Cd

300

450 600

Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.

Circular design in diameter 110mm.

Sandblasted metalized aluminium reflector.

Powder painted die-cast aluminium trim available in assorted finishes.

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0110].

Remote driver supplied. Electronic options for lighting control: DALI/DSI. Passive temperature management: heat dissipation flows through heat sink.

Ceiling-mounted using galvanised steel support with spring clamps.

Light source power: 11.7 W Fixture power: 12.99 W Constant Current: 350 mA

Luminous flux of the light source: 1975lm Luminous flux of the fixture: 1402lm

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam3

Beam Angle: 82° **LOR:** 71%

Average Service Life: 50000h LED reliability: 51000h L80B10

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.55m

Photobiological safety group: 1 Luminous efficacy: 108 lm/W

This product contains a light source of energy efficiency class D

#### **Electronic Equipment**

K: On/Off

D: DALI-2/DSI/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

\*Add the suffix -K, -D, -B after the reference to indicate your electronic equipment choice.

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 7: RAL9006: White Aluminium

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 29.03.2024]

5 years guarantee

