

MINI QUID

Small recessed downlights









101MQD.1-R931















Imax=1290 Cd

500

750

1000





η=100.0% ▼ M ▼ Ø ▼LUX

1.72 1290

8.6 52

323

81

1

3 5.2 143

4 6.9 82°

Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.

Circular design in diameter 110mm.

Sandblasted metalized aluminium reflector.

Powder painted die-cast aluminium trim available in assorted finishes.

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0110].

Remote driver supplied. Electronic options for lighting control: DALI-2. Passive temperature management: heat dissipation flows through heat sink.

Ceiling-mounted using galvanised steel support with spring clamps.

Light source power: 17.2 W Luminaire connected power: 19.13 W Constant Current: 500 mA Light source luminous flux: 2850lm Luminaire luminous flux: 2023lm

CRI: >80

Colour Temperature: 4000K Chromaticity Tolerance: MacAdam3

Beam Angle: 82°

LOR: 71%

Average Service Life: 50000h LED reliability: 48000h L80B10

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.55m

Photobiological safety group: 1 Luminaire efficiency: 106 lm/W

This product contains a light source of energy efficiency class D

Electronic Equipment

K: On/Off (basic)
D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

*Add the suffix -K, -D, -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 25.04.2024]

5 years guarantee



Spain

T. +34 93 881 37 13