

## 122ATM.1-R048



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting.  
Circular design in diameter 190mm.  
Metalized aluminium reflector in assorted finishes: specular or sandblasted depending on the beam angle outcome.  
Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request.  
Glass accessory available to increase the protection rating to IP54 | IK05 from underneath [reference M2.B0190].  
316L stainless steel trim accessory with flush glass and silicone rubber gasket to increase the protection rating to IP65 | IK07 from underneath [reference M2.C0190].  
Drop glass disk accessory available in assorted colours [reference M1.A0190].  
Drop metal disk accessory available in assorted colours [reference M1.B0190].  
LED Module Tunable White: 2700K - 6500K.  
Remote driver supplied.  
Electronic options for lighting control: SwitchDIM/ColourSwitch/DALI/DSI.  
Passive temperature management: heat dissipation flows through aluminium heat sink.  
Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 30mm.


**Fixture power:** 30 W  
**Constant Current:** 500 mA  
**Luminous flux of the light source:** 2050lm  
**CRI:** >90  
**Colour Temperature:** 2700K-6500K  
**Chromaticity Tolerance:** MacAdam 3  
**Average Service Life:** 50000h  
**LED reliability:** 50000h L80B50  
**Photobiological safety group:** 1  
**This product contains a light source of energy efficiency class A+**

**Electronic Equipment**  
**T:** DALI-2/DSI SwitchDIM/ColourSwitch

\*Add the suffix **-T** after the reference to indicate your electronic equipment choice.

**Finishes**  
**2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

### Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 19.04.2024]

#### 5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346  
BSI Cert ISO 14001:2015 - n°EMS 554685

**ROVASI S.L.**  
Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

**Contact**  
T. +34 93 881 35 12 info@rovasi.com  
T. +34 93 881 37 13 [www.rovasi.com](http://www.rovasi.com)