



140GTA.1-I910



Surface mounted downlights with symmetrical light distribution to achieve an effective task or general lighting.

Neutral cylindrical body in diameter 60mm.

Sandblasted metalized aluminium reflector silver finished.

Powder painted aluminium profile available in assorted finishes, customized RAL under request.

Built-in driver, included.

Electronic options for lighting control: DALI/DSI.

Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself.

Mounting to the ceiling plate with two securing points. Cable entry from the top of the fixture.

GOTA can be combined with the KERI pendant line to get a harmonious finish.

Light source power: 4.8 W

Fixture power: 5.32 W

Constant Current: 150 mA

Luminous flux of the light source: 785lm

Luminous flux of the fixture: 589lm

CRI: >90

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 35°

LOR: 75%

Average Service Life: 50000h

LED reliability: 50000h L90B10

UGR: <16

Photobiological safety group: 1

Luminous efficacy: 111 lm/W

This product contains a light source of energy efficiency class E

Electronic Equipment


S: On/Off

D: DALI-2/DSI switchDIM/corridorFUNCTION

*Add the suffix **-S, -D** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White textured, **2:** RAL9005: Jet Black textured, **4:** RAL7016: Anthracite Grey textured, **7:** RAL9006: White Aluminium textured



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 17.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarrà
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com