




143KER.1-I905



Pendant downlights with symmetrical light distribution to achieve an effective task or general lighting.  
Neutral cylindrical body in diameter 60mm.  
Sandblasted metalized aluminium reflector silver finished.  
Powder painted aluminium profile available in assorted finishes, customized RAL under request.  
Built-in driver, included.  
Electronic options for lighting control: DALI-2.  
Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself.  
Delivered with 1 meter steel cord as standard. Transparent electronic wire. Mounted to the ceiling by cylindrical ceiling rose.  
For a more dynamic result, it can be supplied with an adapter for three-phase track [reference M3.A].  
KERI can be combined with the GOTA surface mounted downlights line fixtures to get a harmonious finish.

**Light source power:** 4.8 W  
**Luminaire connected power:** 5.32 W  
**Constant Current:** 150 mA  
**Light source luminous flux:** 845lm  
**Luminaire luminous flux:** 592lm  
**CRI:** >80  
**Colour Temperature:** 2700K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 41°  
**LOR:** 70%  
**Average Service Life:** 50000h  
**LED reliability:** 50000h L90B10  
**UGR:** <16  
**Photobiological safety group:** 1  
**Luminaire efficiency:** 111 lm/W  
**This product contains a light source of energy efficiency class D**



**Electronic Equipment**

**S:** On/Off  
**D:** DALI-2/switchDIM/corridorFUNCTION

\*Add the suffix **-S, -D** after the reference to indicate your electronic equipment choice.

**Finishes**

**1:** RAL9010: Pure White textured, **2:** RAL9005: Jet Black textured, **4:** RAL7016: Anthracite Grey textured, **7:** RAL9006: White Aluminium textured

**Upgradeable, Replaceable, Repairable**



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 25.04.2024]

**5 years guarantee**



BSI Cert ISO 9001:2015 - n°FM 39346  
BSI Cert ISO 14001:2015 - n°EMS 554685

**ROVASI S.L.**  
Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

**Contact**  
T. +34 93 881 35 12 info@rovasi.com  
T. +34 93 881 37 13 www.rovasi.com