




# BAFFLE EVOLUTION SQ

Small recessed downlights

**ROVASI**  
Positive Lighting




101BES.1-R619



Recessed ceiling-mounted small downlight with symmetrical light distribution to achieve an effective accent or ambient lighting.  
 Square design in 100mm x 100mm.  
 Powder painted aluminium anti-dazzle reflector.  
 Black internal baffle for minimal glare.  
 Powder painted die-cast aluminium frame available in assorted finishes, customized RAL under request.  
 Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0100].  
 Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0050].  
 Remote driver included.  
 Electronic options for lighting control: DALI-2.  
 The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.  
 3 hours battery available as option.  
 Passive temperature management: heat dissipation flows through an aluminium heat sink.  
 Ceiling-mounted by spring clamps for easy installation, ceiling thickness up to 25mm.

**Luminaire luminous flux:** 670lm  
**Luminaire connected power:** 7.69 W  
**Luminaire efficiency:** 87 lm/W  
**Light source luminous flux:** 670lm  
**Light source power:** 6.6 W  
**Constant Current:** 200 mA  
**CRI:** >90  
**Colour Temperature:** 3000K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 24°  
**LOR:** 100%  
**Average Service Life:** 50000h  
**LED reliability:** >50000h L70B50  
**UGR:** <16  
**Photobiological safety group:** 1  
**Cd/Klm:** 3746  
**Imax:** 2510 Cd  
**This product contains a light source of energy efficiency class F**



## Electronic Equipment


**K:** On/Off (basic)  
**S:** On/Off (AC/DC)  
**SE:** On/Off (AC/DC) + Battery 3h  
**D:** DALI-2/switchDIM/corridorFUNCTION  
**DE:** DALI-2/switchDIM + 3h battery  
**B:** Bluetooth-Casambi

\*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

## Finishes

**2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

## Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 19.09.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346  
 BSI Cert ISO 14001:2015 - n°EMS 554685

## ROVASI S.L.

Ronda de la Font Grossa, 15  
 Pol. Ind. La Gavarra  
 08540 Centelles | Barcelona  
 Spain

## Contact

T. +34 93 881 35 12 info@rovasi.com  
 T. +34 93 881 37 13 www.rovasi.com