
# **TUNABLE WHITE**




Special Applications









## 105FCS.1-R048



Recessed ceiling-mounted downlight with directional inner light source to achieve an effective task or accent lighting. Adjustable to 30°. Circular design in diameter 190mm. Metalized specular aluminium reflector. Interior reflector in assorted finishes: facetted metalized or sandblasted metalized depending on the beam angle outcome. Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request. LED ring decorative accessory as option [reference F1.B0190]. Glass accessory available to increase the protection rating to IP54 | IK05 from underneath [reference M2.B0190]. 316L stainless steel trim accessory with flush glass and silicone rubber gasket to increase the protection rating to IP65 | IK07 from underneath [reference M2.C0190]. LED module Tunable White: 2700K-6500k. Remote driver supplied. Electronic options for lighting control: DALI/DSI. Passive temperature management: heat dissipation flows through heat pipes. Mounted to the ceiling by three fixing points. Fixture power: 30 W Constant Current: 500 mA Luminous flux of the light source: 2050lm **CRI:** >90 Colour Temperature: 2700K-6500K Chromaticity Tolerance: MacAdam 3 Beam Angle: 16° Average Service Life: 50000h LED reliability: 50000h L80B50 Photobiological safety group: 1 This product contains a light source of energy efficiency class A+ **Electronic Equipment** T: DALI-2/DSI SwitchDIM/ColourSwitch \*Add the suffix -T after the reference to indicate your electronic equipment choice. Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 17.04.2024]

5 years guarantee ERE CE BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

## ROVASI S.L.

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra

08540 Centelles | Barcelona

### Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com